A18

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

09-202843

(43) Date of publication of application: 05.08.1997

(51)Int.CI.

C08L 29/04 C08L 29/04 B32B 27/20 B32B 27/30 B65D 81/24 C08F 8/00 C08F 8/42 C08F216/06 C08K 3/36 C09D129/04

(21)Application number: 08-010871

(71)Applicant: TOPPAN PRINTING CO LTD

(22)Date of filing:

25.01.1996

(72)Inventor: USAMI JINICHI

YOSHINAGA MASANOBU

(54) POLYVINYL ALCOHOL-BASED COMPOSITION AND ITS PRODUCTION

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain the subject composition excellent in resistance to water and moisture, and capable of preserving high gas barrier property inherent in polyvinyl alcohol-based resin even if exposed to a highly humid atmosphere.

SOLUTION: This composition is such a one that an inorganic lamellar compound such as montmorillonite is located at voids in a crosslinked polymer consisting of a modified polyvinyl alcohol-based resin. The inorganic lamellar compound particles can be surely located at the voids of the crosslinked polymer by dissolving the crosslinked polymer in a solvent followed by adding the inorganic lamellar compound in the resultant solution.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]